



.....When Quality is Priority



GeM
Government
e Marketplace





ISO



सूक्ष्म, लघु एवं मध्यम उद्यम
MICRO, SMALL & MEDIUM ENTERPRISES

PRODUCT CATALOGUE

- IP CAMERAS & NVRs
- AHD CAMERAS & DVRs
- CCTV CABLES & CAT-6
- CCTV POWER SUPPLY
- NETWORK POE SWITCHES



MAKE IN INDIA

www.ameego.com

4MP IP CAMERA

AG-DIP-4MP-GOLD



Key Feature:

- 1/2.9" CMOS Image Sensor
- 4 Megapixel Resolution
- Lens 3.6mm Fixed
- Frame Rate 25 fps
- Support: POE
- H.265/H.265+ Dual Stream
- Color Night Vision
- 3DDNR, AGC, AWB,
- BLC Supported

AG-BIP-4MP-GOLD



Key Feature:

- 1/2.9" CMOS Image Sensor
- 4 Mega Pixel Resolution
- Lens 3.6mm Fixed
- Maximum Frame rate 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof

AG-DIP-4MP-DARKLIGHT



Key Feature:

- Face Detection
- 1/2.7" CMOS Image Sensor
- 4 Megapixel Resolution
- Lens 4mm
- Maximum 25 fps
- Support: POE
- H.265/H.265 Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- Support Audio In-Out
- Dual Light

AG-BIP-4MP-DARKLIGHT



Key Feature:

- Face Detection
- 1/2.7" CMOS Image Sensor
- 4 Megapixel Resolution
- Lens (6mm opt.)
- Maximum 25 fps
- Support: POE
- H.265/H.265 Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio In-Out
- Dual Light

5MP IP CAMERA

AG-DIP-5MP-GOLD



Key Feature:

- 1/2.9" CMOS Image Sensor
- 5 Megapixel Resolution
- Lens 3.6mm Fixed
- Maximum Frame rate 20 fps
- Support: POE
- H.265/H.265+ Dual Stream
- Color Night Vision
- 3DDNR, AGC, AWB,
- BLC Supported

AG-BIP-5MP-GOLD



Key Feature:

- 1/2.9" CMOS Image Sensor
- 5 Megapixel Resolution
- Lens 3.6mm Fixed
- Maximum Frame rate 20 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof

AG-DIP-5MP-DARKLIGHT



Key Feature:

- Face Detection
- 1/2.9" SONY Image Sensor
- 5 Megapixel Resolution
- Lens 4mm
- Maximum Frame rate 25 fps
- Support: POE
- H.265/H.265 Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- Support Audio In-Out
- Dual Light

AG-BIP-5MP-DARKLIGHT



Key Feature:

- Face Detection
- 1/2.9" SONY Image Sensor
- 5 Megapixel Resolution
- Lens 4mm (6mm Option.)
- Maximum Frame rate 25 fps
- Support: POE
- H.265/H.265 Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio In-Out
- Dual Light

8MP IP CAMERA

AG-DIP-8MP-GOLD



Key Feature:

- 1/2.8" CMOS Image Sensor
- 8 Megapixel Resolution
- Lens 3.6mm Fixed
- Frame Rate 20 fps
- Support: POE
- H.265/H.265+ Dual Stream
- Color Night Vision
- 3DDNR, AGC, AWB,
- BLC Supported

AG-BIP-8MP-GOLD



Key Feature:

- 1/2.8" CMOS Image Sensor
- 8 Mega Pixel Resolution
- Lens 3.6mm Fixed
- Maximum Frame rate 20 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof

AG-DIP-8MP-DARKLIGHT



Key Feature:

- Face Detection
- 1/2.8" SONY Image Sensor
- 8 Megapixel Resolution
- Lens 4mm
- Maximum 25 fps
- Support: POE
- H.265/H.265 Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- Support Audio In-Out
- Dual Light

AG-BIP-8MP-DARKLIGHT



Key Feature:

- Face Detection
- 1/2.8" SONY Image Sensor
- 8 Megapixel Resolution
- Lens 4mm (6mm Optional.)
- Maximum 25 fps
- Support: POE
- H.265/H.265 Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio In-Out
- Dual Light

5/8MP IP MOTORIZED CAMERA

NEW

AG-IP-5MP-MVF 50MTR IR



Key Feature:

- 1/2.8", 5 Mega Pixel CMOS Image Sensor
- Lens (MOTERISED 2.8mm TO 12MM.)
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-65 Weather-proof
- Support Audio Optional
- Dual Light

NEW

AG-IP-8MP-MVF 50MTR IR



Key Feature:

- 1/2.8", 8 Mega Pixel CMOS Image Sensor
- Lens (MOTERISED 2.8mm TO 12MM.)
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-65 Weather-proof
- Support Audio Optional
- Dual Light

4/5MP IP CAMERA (6/8MM) LENS

AG-IP-4MP-6MM / 8MM



Key Feature:

- 1/2.7", 4 Mega Pixel CMOS Image Sensor
- Lens 6mm / 8mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

AG-IP-5MP-6MM / 8MM



Key Feature:

- 1/2.7", 5 Mega Pixel CMOS Image Sensor
- Lens 6mm / 8mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

4/5MP IP CAMERA (12MM) LENS

AG-IP-4MP-6MM / 8MM



Key Feature:

- 1/2.7", 4 Mega Pixel CMOS Image Sensor
- Lens 12mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

AG-IP-5MP-6MM / 8MM



Key Feature:

- 1/2.7", 5 Mega Pixel CMOS Image Sensor
- Lens 12mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

10/16 CHANNEL NVR

AG-NVR-10CH-H265-4K

Support access of multiple AMEEGO smart IP Cameras with human detection and face detection function.



Key Feature:

- Support Camera: 1080p , 4mp, 5mp, 8mp
- Communication: LAN+USB
- IP PTZ: Support
- Motion Recording: Yes
- Output: VGA+HDMI
- USB Port: 2 Port
- Backup: USB+LAN
- Protocol: Support ONVIF;access third party;
- Encoding Format: H.265/H.264
- HDD Support: 1 SATA port Upto - 10 TB

AG-NVR-16CH-H265-4K

Support access of multiple AMEEGO smart IP Cameras with human detection and face detection function.



Key Feature:

- Recording: 25fps
- Support Camera: 1080p , 4mp, 5mp, 8mp
- Communication: LAN+USB
- IP PTZ: Support
- Motion Recording: Yes
- Output: VGA+HDMI
- USB Port:2 Port
- Backup: USB+LAN
- Protocol: Support ONVIF;access third party;
- Encoding Format: H.265/H.264
- HDD Support: 1 SATA port Upto - 10 TB

36/64 CHANNEL NVR

AG-NVR-36CH-H265-4K

Support access of multiple AMEEGO smart IP Cameras with human detection and face detection function.



Key Feature:

- Processor : NT98332
- Video Input : 36CH4K
- Encoding Format:H.265AI/H.265+
- Backup: USB, LAN, SATA
- Protocol: Support ONVIF;access third party;
- Backup : Network ,USB , SATA
- HDD Support: 2 SATA port Upto - 14 TB
- HDMI output: 1*HDMI (MAX 4K)
- VGA output : 1*VGA (1080P)

AG-NVR-64CH-H265-4K

Support access of multiple AMEEGO smart IP Cameras with human detection and face detection function.



Key Feature:

- Processor : NT98336
- Video Input : 64CH4K
- Encoding Format:H.265AI/H.265+
- Backup: USB, LAN, SATA
- Protocol: Support ONVIF;access third party;
- Backup : Network ,USB , SATA
- HDD Support: 8 SATA port Upto - 14 TB
- HDMI output: 2*HDMI (MAX 4K)
- VGA output : 1*VGA (1080P)

IP LONG DISTANCE PTZ CAMERA

HDC-IP-4MP-PTZ



Key Feature:

- 4MP, 36X Zoom
- Zoom Display 36X, Neutral Package
- 6 inch, Half Metal Body Construction, IP66
- IP-PTZ AI Medium speed dome
- IR Sidtance Up to 150 meters
- Wall Mount Bracket, DC12V Power Supply

HDC-IP-5MP-PTZ



Key Feature:

- 5MP, 36X Zoom
- Zoom Display 36X, Neutral Package
- 7 inch, Half Metal Body Construction, IP66
- IP-PTZ AI Medium speed dome
- IR Sidtance Up to 200 meters
- Wall Mount Bracket, DC12V Power Supply

HDC-IP-6MP-PTZ



Key Feature:

- 6MP, 36X Zoom
- Zoom Display 36X, Neutral Package
- 10 inch, Half Metal Body Construction, IP66
- IP-PTZ AI Medium speed dome
- IR Sidtance Up to 150 meters
- Wall Mount Bracket, DC12V Power Supply

4/8 CHANNEL DVR

AG-4CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 4 Ch(5mp)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 1 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

AG-8CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 8Ch(5mp)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 1 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

16/32 CHANNEL DVR

AG-16CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 16Ch (5mp)
- Video Compression: H.264
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 2 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

AG-32CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 32Ch (5mp)
- Video Compression: H.264
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 4 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

HD 2.4 IR DOME & BULLET CAMERA

AG-IR-2.4-D



2.4MP DOME

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m IR Distance
- Multiple Angle Adjustable

AG-IR-2.4-T



2.4MP BULLET

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6/6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m IR Distance
- Multiple Angle Adjustable

AG-IR-5MP-D



5MP DOME

- 1/3", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m IR Distance
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

AG-IR-5MP-T



5MP BULLET

- 1/3", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm/6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m IR Distance
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

2.4MP HD COLOR CAMERA

2.4MP AG-AHD-CV-2.4-D



Key Feature:

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m White Light
- Multiple Angle Adjustable

2.4MP AG-AHD-CV-2.4-T



Key Feature:

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6/6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m White Light
- Multiple Angle Adjustable

2.4MP AG-AHD-CV-2.4-DA



Key Feature:

- 1/2.9", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m White Light
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

2.4MP AG-AHD-CV-2.4-TA



Key Feature:

- 1/3", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm/6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m White Light
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

5MP HD COLOR CAMERA

5 MP AG-AHD-CV-05-D



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable

5 MP AG-AHD-CV-05-T



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable

5 MP AG-AHD-CV-05-DA



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable
- With Inbuilt Audio Mic

5 MP AG-AHD-CV-05-TA



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable
- With Inbuilt Audio Mic

CCTV CABLES & NETWORK CABLES

INDOOR CAT6 CABLE
(100/305Mtr.)



Key Feature:

- 4 Pair
- 24 AWG
- Weather Proof Single Jacket
- Solid 100% Copper
- Colors: Green , Red, Grey, Yellow

OUTDOOR CAT6 CABLE
(100/305Mtr.)



Key Feature:

- 4 Pair
- 24 AWG
- Weather Proof Double Coated
- Solid 100% Copper
- Colors: Green , Red, Grey, Yellow

INDOOR 3+1 CABLE



Key Feature:

- No of Core: 3
- Insulation: PVC
- Copper Gauge: 20/22/26/28
- Video Core insulation: HDPE
- Color Video Code: Natural
- Color of Jacket: white
- Shielded: AL-Mylar
- Sequential marking: Every Meter

OUTDOOR 3+1 CABLE



Key Feature:

- No of Core: 3
- Insulation: Weatherproof Double Coated
- Copper Gauge: 20/22/26/28
- Video Core insulation: HDPE
- Color Video Code: Natural
- Color of Outer/Inner Jacket: Black/White
- Shielded: AL-Mylar
- Sequential marking: Every Meter

SMPS POWER SUPPLY

AG-PS04-SINGLE



Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 200 mA @230V
- Output current : 4800 mA Max.

AG-PS04-SINGLE



Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 290 mA @230V
- Output current : 7200 mA Max

AG-PS04-SINGLE



Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 590 mA @230V
- Output current : 9600 mA Max.

AG-PS04-MULTI



Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 200 mA @230V
- Output current : 4800 mA Max.

AG-PS08-MULTI



Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 290 mA @230V
- Output current : 7200 mA Max

AG-PS16-MULTI



Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 590 mA @230V
- Output current : 9600 mA Max.

NETWORK POE SWITCH

UPLINK POE SWITCH (10/100/1000)MBPS

4-PORT



AG-POE-42N

- PoE Ethernet 4*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 100Mbps
- Consumption: 75W(52V 1.44A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 1.2Gbps
- Throughput: 0.9Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 0.95Kg

SPEED
10/100MBPS

8-PORT



AG-POE-82N

- PoE Ethernet 8*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 100Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 2Gbps
- Throughput: 1.488Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 0.95Kg

SPEED
10/100MBPS

8-PORT



AG-POE-82NGS

- PoE Ethernet 8*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 100Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 5.6Gbps
- Throughput: 4.1664Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 1.05Kg

SPEED
10/100/1000MBPS

16-PORT



AG-POE-1621GS

- PoE Ethernet 16*Port: 10/100Mbps
- Uplink + SFP 2+1*Port: 1000Mbps
- Consumption: 250W(52V 4.8A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 7.6Gbps
- Throughput: 5.6544Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 4.2Kg

SPEED
10/100/1000MBPS

24-PORT



AG-POE-24N2G2S

- PoE Ethernet 24*Port: 10/100Mbps
- Uplink + SFP 2+2*Port: 1000Mbps
- Consumption: 300W(52V 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 12.8Gbps
- Throughput: 9.5232Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 5.2Kg

SPEED
10/100/1000MBPS

FULL GIGA POE SWITCH (1000)MBPS

4-PORT



AG-POE-41FGS

- PoE Ethernet 4*Port: 1000Mbps
- Uplink & SFP Port 1+1: 1000Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 12Gbps
- Throughput: 8.928Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 1.05Kg

SPEED
1000MBPS

8-PORT



AG-POE-82FGS

- PoE Ethernet 8*Port: 1000Mbps
- Uplink & SFP 2+2*Port: 1000Mbps
- Consumption: 150W(52V 2.88A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 20Gbps
- Throughput: 14.88Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 2.5Kg

SPEED
1000MBPS

FULL GIGA POE SWITCH (1000)MBPS

16-PORT



AG-POE-162G1SF

- PoE Ethernet 16*Port: 1000Mbps
- Uplink + SFP 2+1*Port: 1000Mbps
- Consumption: 300W(52V 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 38Gbps
- Throughput: 29.41Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 4.2Kg

SPEED
1000MBPS

24-PORT



AG-POE-24G1G2GSF

- PoE Ethernet 24*Port: 1000Mbps
- Uplink & SFP 2+2*Port: 1000Mbps
- Consumption: 300W(52V 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 56Gbps
- Throughput: 43.34Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 5.68Kg

SPEED
1000MBPS



Network Based Video Door Phone Bell with 10" Touch Screen

MODEL: AMG-IPV4F

Monitor: 7/10" IPS Touch Screen | Resolution: 1080P | WiFi: 2.4G | Memory: Built-in 5MB Storage.max up 128GB
Intercom Mode: 2-Way Communication / Tuya APP | Camera Sensor: 2.0MP | View Angle: 120* | LEDS For Night
LED: IR Night Vision | Waterproof: Ip65 | Power Consumption: Standbys2W Working ≤ 5W | Power Supply: From
Monitor Supply or Poe Switch



Tuya
Mobile App

RFID KEY



VDP

VIDEO DOOR PHONE

Network Based Video Door Phone
Bell with 10" Touch Screen



Tuya
Mobile App

MODEL: AMG-IPV1F

Monitor: 7/10" IPS Touch Screen | Resolution: 1080P
WiFi: 2.4G | Memory: Built-in 5MB Storage.max up 128GB
Intercom Mode: 2-Way Communication / Tuya APP
Camera Sensor: 2.0MP | View Angle: 120* | LEDS For Night
LED: IR Night Vision | Waterproof: Ip65 | Power Consumption:
Standbys2W Working ≤ 5W | Power Supply: From Monitor
Supply or Poe Switch

ELECTRIC RIM LOCK




Features:

5 Digital Keys Door lock | Digital Computerised Key | Slot cut at back side for easy adjustment | 5 Computerised keys | Easy latch reversible for Right hand and left hand door lock opening | Both Side opening by Key | Local opening by push button | Lock push button operation by key | Brass Roller and Brass reversible latch | Heavy Duty 2KG weight lock | Universal Lock - Left Side Gate Right Side Gate both Way Open | Unique Latch Reverse function to make lock suitable for Right hand | or left hand opening gate without opening the lock



.....When Quality is Priority



**MAKE
IN INDIA**



www.ameego.com



CE FC RoHS COMPLIANT ISO